



#### PRODUCT INFO:

- **Housing material:** galvanized steel, stainless steel
- **Installation:** bayonet
- **Typ od seal:** PE
- **Operating temperature:** up to 80 °C
- **Disposal:** can be disposed of in incinerators or municipal waste landfill
- **Warranty:** valid for the entire service life of the filter

#### GENERAL DESCRIPTION:

- **Application:** odor removal from kitchens, extraction from welding, soldering, painting, and industrial, chemical, and electrotechnical production.
- **Mounting option:** G16, G12, G8, G4



#### ACTIVATED CARBON FILTER CARTRIDGES

| Cartridge type/size           | 450      | 600      | BIG       |
|-------------------------------|----------|----------|-----------|
| Outer diameter                | 145 mm   | 145 mm   | 367 mm    |
| Height/Length                 | 450 mm   | 600 mm   | 1003 mm   |
| Weight of activated carbon    | 2,1 kg   | 3 kg     | 25 kg     |
| Thickness of carbon core      | 26 mm    | 26 mm    | 26 mm     |
| Max. relative humidity        | 70 %     | 70 %     | 70 %      |
| Maximum airflow               | 190 m³/h | 190 m³/h | 1800 m³/h |
| Time to reach maximum airflow | 0,1 sec  | 0,1 sec  | 0,1 sec   |

